

Skeeter *Brush Trucks*



Type 5/6

Loaded with flexibility, the way you need it.

- Simple to operate, easy to maintain, and maximize truck efficiency
- High mobility apparatus fights offensively with minimal manpower
- Available on most commercial chassis (Ford, Ram, International or Freightliner)
- Skeeter ATP™ includes: 6" lift, 20" super-single tires & wheels, and skid-plateing
- Industry leading 5-year parts & labor warranty and 10 year structural warranty



Flat-Bed



Step-Side



Rescue-Side

SkeeterBrushTrucks.com

SKEETER TYPE 5/6 WILDLAND ENGINE

GENERAL

- NWCG Type 5/6 Compliant Base Vehicle
- Equipment Capacity—500#
- 4,500# Reserve, Fully Loaded Weight (2 Firefighters)
- All Designs Reviewed by In-House Structural Engineer
- High Capacity/Articulation Suspension & Body System
- Field Serviceable Valves/Plumbing

VARIATIONS

- Flat-Bed (114" x 92" or 96")
- Step-Side (114" x 92" or 96")
- Rescue-Side (114" x 92" or 96")
- Hybrid (114" x 92" or 96")

CHASSIS

- 2 Door, Super Cab, 4 Door, Gas and Diesel
- 19,500 or 23,000 lb. GVWR
- Extreme Service Off-Road Bumper
- 60" Cab to Axle, 40 Gallon Fuel Tank
- 300 Horse Power, 660 Ft Lbs Torque
- Automatic Transmission
- Electronic 4x4 Shift-On-The-Fly, Auto. Locking Hubs
- Power Steering and Brakes
- 40/20/40 Seats
- Trailer Tow Mirrors Front
- AM/FM/CD Radio

CHASSIS MODIFICATIONS

- 6" Suspension System
- Load Range M Super Single Radial Tires (5)
- 4.88 Gears
- Limited Slip Rear Differential
- Front and Rear Tow Eyes
- Rear Mud Flaps
- Cab/Body Steps
- Radiator/Front of Engine Skid Plate
- Transfer Case Skid Plate

PUMP

- Auxiliary Pump Gas or Diesel 100-300 gpm
- PTO Pump 100-500 gpm
- Custom Pump Panel, 2.5" Pressure Gauge
- Exhaust or Electric Primer
- Fuel, Removable, Stainless, or to Chassis
- Stainless Steel Valves and Plumbing

INTAKES/DISCHARGES

- 2.5" Gated Intake with Cap
- 2.5" Gated Tank to Pump Line
- 1" Gated Tank Fill / Recirculate Line
- 2.5" Rear Gated Discharge w/1.5" Reducer
- 1" Hose Reel, 150', 300 psi rated
- 1" Whip Lines, 8' (2)
- .75" Discharge
- (2) Ground Sweeps, Front Bumper, Elec. Controlled
- 1.5" Front Monitor, Remote Controlled in Cab
- 150' Aluminum Electric Rewind Booster Reel

TANK

- 100 - 500 Gallon Poly. Tank w/sight gauge
- 10-20 Gallon Integral Foam Tank
- Tank Fill & Overflow Tower w/Cover
- 4 LED Tank Level Gauges (2 Cab & 2 Panel)
- Lifetime Tank Warranty

FOAM SYSTEMS

- Through-the-Pump Class A
- Injected Class A
- Compressed Air Foam (CAFS)

BODY AND COMPARTMENTS

- 114" x (92" or 96") Custom Aluminum Body
- 5" Mainframe, 3" Cross Members on 12" Centers
- 1/8" Aluminum Diamond Plate Floor
- Spring Mounted Body System
- Headache Bar w/Light Bar Platform
- 33" x 5" x 96" Rear Compartment & Slide-Out Tray
- Swing or Roll-Up Compartment Doors
- (2) 48" x 18" x 24" Aluminum Compartments
- (2) 24" x 48" x 24" Aluminum Compartments
- Rear Body Access Steps or Tailboard
- Hose Tray for 200' 1.5" Hose
- Under Body Hard Suction Storage / Long Tool Tray
- Turtle Tile Compartments & Trays

12 VOLT ELECTRICAL

- 20" x 18" x 4" Body Electrical Wiring Enclosure
- Whelen Legacy LED Light Bar / Scene Lights
- Whelen LED Traffic Advisor
- Whelen M7 LED Emergency Lights
- Whelen M6 Signal LED Stop/Tail/Turn Signals
- Rigid Technologies LED Scene Lighting (4-Sides)
- LED Marker Lights
- LED Cab Ground Lights
- LED Compartment Lights
- LED Step Lights
- LED License Plate Light and Bracket
- Backup Alarm
- Door Ajar Light
- Electronic Master Disconnect System
- Whelen or FRC Scene Lighting Packages

SIREN/SPEAKERS/INTERCOM

- Whelen CENCOM Control Module & Electronic Siren
- Whelen 100 Watt Speaker
- Wired or Wireless Intercom System

STRIPING/GRAPHICS

- 4" Cab and Body Stripe
- Front & Rear NFPA Reflective Chevrons,

EQUIPMENT

- TFT Adjustable Bubble Cup Nozzles (3)
- Hydrant Wrench/Spanner Set
- NWCG Compliant Equipment Provided



SCBA / EMS In-Cab



Stainless Steel Plumbing



LED Scene Lights



Sealed Electrical



Hard Suction Storage